



ConCab kabel gmbh

CC-single core Nonflam-329

单芯，耐高温至 +450° C

high temperature resistant up to +450° C



应用领域

CC-single core Nonflam-329 适用于极端高温区域的布线设备，耐高温达 450° C。尤其是需要用在暖气装置散热器，家用加热设备中，以及重工业如铸造厂、炼钢炉、玻璃生产和所有其它类似的钢铁厂中。

application

The CC-single core nonflame-329 is excellent for wiring equipment in areas with extremely high temperatures of up to 450° C. This is necessary for the installation of radiators, household heating appliances as well as in heavy industries like foundries, steel melting furnaces, glass production and in all other kinds of steel works.

构造

纯镍丝精绞，多层纤维玻璃绝缘，带矿物浸渍纤维编织层包覆，无卤型。外护套颜色灰色。其它颜色可根据要求定制。

construction

Fine strands of nickel wires, multilayered fiber glass insulation covered with mineral impregnated braiding. Colour grey. Other colours are available on request.

技术数据 / technical data

额定电压 / rated voltage:

300/500 V

测试电压 / test voltage:

2.000 V

导体绞合方式 / conductor stranding:

纯镍精绞 /

fine strands of pure nickel,

温度范围 / temperature range:

固定安装 / fixed installation:

-60° C 至 /to +450° C

短时耐温 / short-term:

+600° C

弯曲半径 / bending radius:

固定安装 / fixed installation:

20 x d 外径 -Ø / outer-Ø

物料编码 part-no.	芯线数 / 导体截面积 no. of cores / cross-section	外径 outer-Ø d mm	重量 weight kg/km
329 0002 05	0,25	2,2	7
329 0005 05	0,50	2,5	9
329 0007 05	0,75	2,7	12
329 0010 05	1,0	3,2	15
329 0015 05	1,5	3,4	21
329 0025 05	2,5	4,0	33
329 0040 05	4	4,5	51
329 0060 05	6	5,3	73
329 0100 05	10	8,0	130
329 0160 05	16	9,4	206
329 0250 05	25	10,6	323
329 0350 05	35	13,4	423
329 0500 05	50	14,0	590